


Low-Voltage JC Bi-Pin Halogen Lamps

- Operating Voltage: 6V/12V/24V
- Average Lifetime: 2000 hours
- Options:
 - Axial filament
 - Gold-plated pins
 - Frosted glass
 - UV-stop version



| Code | Model | M.O.L (mm) | L.C.L (mm) | Base | Luminous Flux (lm) | Packing pcs/ctn(cm) | G .W. (Kg/ctn) |
|----------------------|-------------|---------------|---------------|----------|-----------------------|------------------------|-------------------|
| 6V JC Bi-Pin | | | | | | | |
| HB 0105 | JC-6V/5W | 33 | 19.5 | G4/BA9s | 65 | 1000/66x32x26 | 6.0 |
| HB 0110 | JC-6V/10W | 33 | 19.5 | G4/BA9s | 130 | 1000/66x32x26 | 6.0 |
| HB 0115 | JC-6V/15W | 33 | 19.5 | G4/BA9s | 200 | 1000/66x32x26 | 6.0 |
| HB 0120 | JC-6V/20W | 33 | 19.5 | G4/BA9s | 270 | 1000/66x32x26 | 6.0 |
| HB 0135 | JC-6V/35W | 33 | 19.5 | G4/G6.35 | 480 | 1000/66x32x26 | 6.0 |
| 12V JC Bi-Pin | | | | | | | |
| HB 0205 | JC-12V/5W | 33 | 19.5 | G4/BA9s | 65 | 1000/66x32x26 | 6.0 |
| HB 0210 | JC-12V/10W | 33 | 19.5 | G4/BA9s | 130 | 1000/66x32x26 | 6.0 |
| HB 0215 | JC-12V/15W | 33 | 19.5 | G4/BA9s | 200 | 1000/66x32x26 | 6.0 |
| HB 0220 | JC-12V/20W | 33 | 19.5 | G4/BA9s | 270 | 1000/66x32x26 | 6.0 |
| HB 0235 | JC-12V/35W | 44 | 19.5 | G4/G6.35 | 480 | 1000/66x32x26 | 7.0 |
| HB 0250 | JC-12V/50W | 44 | 30.0 | G6.35 | 900 | 1000/66x32x26 | 7.0 |
| HB 0275 | JC-12V/75W | 44 | 30.0 | GY6.35 | 1300 | 1000/66x32x26 | 7.0 |
| HB 021A | JC-12V/100W | 44 | 30.0 | GY6.35 | 1800 | 1000/66x32x26 | 8.2 |
| 24V JC Bi-Pin | | | | | | | |
| HB 0305 | JC-24V/5W | 33 | 19.5 | G4/BA9s | 85 | 1000/66x32x26 | 6.0 |
| HB 0310 | JC-24V/10W | 33 | 19.5 | G4/BA9s | 170 | 1000/66x32x26 | 6.0 |
| HB 0315 | JC-24V/15W | 33 | 19.5 | G4/BA9s | 250 | 1000/66x32x26 | 6.0 |
| HB 0320 | JC-24V/20W | 33 | 19.5 | G4/BA9s | 340 | 1000/66x32x26 | 6.0 |
| HB 0335 | JC-24V/35W | 44 | 30.0 | G6.35 | 600 | 1000/66x32x26 | 7.0 |
| HB 0350 | JC-24V/50W | 44 | 30.0 | G6.35 | 850 | 1000/66x32x26 | 7.0 |
| HB 0375 | JC-24V/75W | 44 | 30.0 | GY6.35 | 1400 | 1000/66x32x26 | 8.2 |
| HB 031A | JC-24V/100W | 44 | 30.0 | GY6.35 | 2000 | 1000/66x32x26 | 8.2 |
| HB 031B | JC-24V/150W | 50 | 30.0 | GY6.35 | 3000 | 1000/66x32x26 | 8.5 |